

# PX2-NRC-1142

## PixiePro™ Networked Room Controller & Control Pucks

The possibilities are endless...



### FEATURES

The Networked Room Controller functions as an independent, web-enabled controller for any display device. With a robust Ethernet interface, it makes configuring, controlling, and monitoring equipment on your network easy—no expensive programming is required. Ideal for monitoring multiple rooms, scheduling, and digital signage applications.

#### ALL YOU NEED FOR THE SIMPLE ROOM

Includes one bidirectional RS-232 control port, one infrared (IR) control port, four low-voltage relays for screens or lifts, and two general purpose sense ports for security and theft detection.

#### SIMPLIFIED WIRING

Includes adapters for common pinouts of 9-pin or 15-pin D-Sub RS-232 control ports on most modern display devices.

#### LIGHTWEIGHT, ATTRACTIVE, LOW-PROFILE

Easily attaches to virtually any display device and blends into the decor of any room.

#### WEB-BASED CONFIGURATION, CONTROL, MONITORING, AND MANAGEMENT

Configured through a friendly AJAX-powered web interface, which supports both SP Controls' extensive library of Drivers, and on-the-fly Driver creation and customization (new IR codes can be learned with a paired PixiePro Modular Panel).

#### VERSATILE AND EXPANDABLE

Designed to seamlessly integrate with the PixiePro line of products to provide a complete solution that is flexible and expandable for virtually any room configuration and any budget.



**Simple  
and  
Intuitive**

SP Controls, Inc.  
930 Linden Avenue  
South San Francisco  
California 94080  
phone: (877) 367-8444  
fax: (650) 392-7881  
email: help@spcontrols.com

### TECHNICAL SPECIFICATIONS

#### Networked Room Controller

Dimensions:	1.44" (h) x 5.44" (w) x 4.5" (d)
Weight:	6.1 oz
Power Supply:	12V, 1.25A
Package Type:	Plastic enclosure

#### Control Pucks

Dimensions:	.75" (h) x 2.7" (w) x 2.7" (d)
Weight:	3.0 oz
Power Supply:	Powered directly off the NRC
Package Type:	Steel enclosure
Output Type:	RS232, IR, dry contact closure (depending on model)
Recommended Wire:	CAT5